

Quick testing of random variables

Antal Iványi,^a Imre Kátai^a

^a Eötvös Loránd University, Dept. of Computer Algebra
E-mail: tony@compalg.inf.elte.hu
E-mail: katai@compalg.inf.elte.hu

Abstract

Let ξ be a random integer vector, having uniform distribution

$$\mathbf{P}\{\xi = (i_1, i_2, \dots, i_n) = 1/n^n\} \text{ for } 1 \leq i_1, i_2, \dots, i_n \leq n.$$

A realization (i_1, i_2, \dots, i_n) of ξ is called *good*, if its elements are different. We present efficient comparison-based algorithms which decide whether a given realization is good [1, 2, 3, 4, 5, 6, 7].

Keywords: random sequences, effective algorithms

MSC 2010: 68Q25, 68Q87, 68R05

References

- [1] Bailey, R. A., Cameron, P. J., Connelly, R., Sudoku, gerechte designs, resolutions, affine space, spreads, reguli, and Hamming codes. *Amer. Math. Monthly*, Vol. 115 (2008), no. 5, 383-404.
- [2] BEHRENS, W. U. Feldversuchsanordnungen mit verbessertem Ausgleich der Bodenunterschiede, *Zeitschrift für Landwirtschaftliches Versuchs- und Untersuchungswesen*, Vol. 2, (1956), no. 2, 176-193.
- [3] CROOK, J. F. A pencil-and-paper algorithm for solving Sudoku puzzles. *Notices Amer. Math. Soc.*, Vol. 56 (2009), no. 4, 460-468.
- [4] IVÁNYI, A., KÁTAI, I. Estimates for speed of computers with interleaved memory systems, *Annales Univ. Sci., Budapest., Sectio Mathematica*, Vol. 19 (1976), 159-164.
- [5] KNUTH, D. E., *The Art of Computer Programming. Vol. 1. Fundamental Algorithms* (third edition). Addison-Wesley, 1997.
- [6] THOM, D., SUDOKU ist NP-vollständig. PhD Dissertation. Stuttgart, 2007.
- [7] XU, C., XU, W., The model and algorithm to estimate the difficulty levels of Sudoku puzzles. *J. Math. Res.*, Vol. 11 (2009), no. 2, 43-46.